



5/A  
1-19-00  
NP

PATENT APPLICATION  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Gordon F. Grigor et. al.

Examiner: Kevin Nguyen

Serial No: 09/032,863

Art Group: 2774

Filing Date: 3/02/98

Docket No: ATI980044

Title: METHOD AND APPARATUS FOR CONFIGURING MULTIPLE DISPLAYS  
ASSOCIATED WITH A COMPUTING SYSTEM

Date: 01/13/2000

Honorable Commissioner of  
Patents and Trademarks,  
Washington, D.C. 20231

RECEIVED  
JAN 19 2000  
TC 2774 MAIL ROOM

**RESPONSE TO OFFICE ACTION UNDER 37 CFR § 1.111**

In response to an Office Action mailed October 13, 1999 regarding the above patent application, the applicant respectfully submits the following response.

**AMENDMENT**

Please amend the following claims as indicated:

1. (Amended) A method for configuring multiple displays with a computing system, the method comprises the steps of:

(a) receiving, a coupling controller, display preferences regarding at least one of the multiple displays;

(b) determining, the coupling controller, whether the display preferences can be fulfilled in observance of at least one of: configuration properties of the at least one of the multiple displays and configuration properties of the computing system; and

al  
cont

Handwritten signature/initials.

(c) when the display preferences can be fulfilled, configuring, the coupling controller, the computing system and the at least one of the multiple displays in accordance with the display preferences.

as  
amended

14. A video graphics processing circuit comprises:

Sub  
B1

a plurality of display controllers included on a single video graphics card;

memory, wherein at least a portion of the memory is screen memory;

a2

coupling module operably coupled to the plurality of displays and the screen memory; and

a coupling controller operably coupled to receive display preferences and to determine whether the display preferences can be fulfilled in observance of configuration properties, wherein, when the display preferences can be fulfilled, the coupling controller provides configuration requirements to the coupling module, wherein the coupling module, based on the configuration requirements, operably couples at least one of the plurality of display controllers with at least a portion of the screen memory and with at least one display, and wherein the at least one of the plurality of display controllers retrieves display data from the at least a portion of the screen memory and provides the display data to the at least one display.

Sub  
B2  
a3  
cont

24. (Amended) A video graphics processing circuit comprises:

a processing unit; and

memory operably coupled to the processing unit, wherein the memory stores programming instructions that, when executed by processing unit, cause a coupling

*a3  
concl'd*

controller of the processing unit to (a) receive display preferences regarding at least one of a multiple displays; (b) determine whether the display preferences can be fulfilled in observance of at least one of: configuration properties of the at least one of the multiple displays and configuration properties of a computing system; and (c) configure the computing system and the at least one of the multiple displays in accordance with the display preferences when the display preferences can be fulfilled.

---

*Sub  
B3*

33. (Amended) A digital storage medium for storing programming instructions that, when executed by a processing unit, cause the processing unit to configure multiple displays associated with a computing system, the digital storage medium comprises:

*a4*

first means for storing programming instructions that cause a coupling controller of the processing unit to receive display preferences regarding at least one of the multiple displays;

second means for storing programming instructions that cause the coupling controller of the processing unit to determine whether the display preferences can be fulfilled in observance of at least one of: configuration properties of the at least one of the multiple displays and configuration properties of the computing system; and

third means for storing programming instructions that cause the coupling controller of the processing unit to configure the computing system and the at least one of the multiple displays in accordance with the display preferences when the display preferences can be fulfilled.

---

**REMARKS**